


AWDC—STAINLESS STEEL WORM DRIVE CLAMP



PN	d	D	Thickness		P	HOSE OD	STANDARD LENGTH
	mm	mm	mm	mm	mm	Nm	Nm
AWDC-15	15	45	0.6	14.2	20	6	9
AWDC-16	16	27	0.6	14.2	20	6	9
AWDC-20	20	32	0.7	15.8	23.5	12	15
AWDC-25	25	45	0.7	15.8	23.5	12	15
AWDC-32	32	44	0.7	15.8	23.5	12	15
AWDC-32	32	52	0.7	15.8	23.5	12	15
AWDC-40	40	60	0.7	15.8	23.5	12	15
AWDC-45	45	65	0.7	15.8	23.5	12	15
AWDC-50	50	70	0.7	15.8	23.5	12	15
AWDC-50	50	75	0.7	15.8	23.5	12	15
AWDC-57	57	79	0.7	15.8	23.5	12	15
AWDC-70	70	92	0.7	15.8	23.5	12	15
AWDC-83	83	106	0.7	15.8	23.5	12	15
AWDC-95	95	118	0.7	15.8	23.5	12	15
AWDC-108	108	130	0.7	15.8	23.5	12	15
AWDC-121	121	143	0.7	15.8	23.5	12	15
AWDC-133	133	156	0.7	15.8	23.5	12	15
AWDC-146	146	188	0.7	15.8	23.5	12	15
AWDC-184	184	208	0.7	15.8	23.5	12	15
AWDC-210	210	232	0.7	15.8	23.5	12	15
AWDC-220	220	240	0.7	15.8	23.5	12	15

